



uPVC General Purpose Duct

uPVC general purpose duct is a single wall pipe manufactured under ISO 9001:2015. uPVC general purpose duct is produced with inbuilt push-fit sockets, using an unsealed system.

Material	Un-plasticised Polyvinyl Chloride (uPVC)
Colour	Available in black/grey. Other colours available on request.
Marking	NAYLOR GP DUCT SIZE dd-mm-yy HH:MM
Quality System & Inspection	All quality systems and inspection procedures comply with BS EN ISO 9001: 2015
Standards & Certification	Does not meet the requirements of BS EN 61386-24:2010
Packaging	Supplied in 6 metre lengths as standard in timber framed packs (quantity of product per packaged unit is dependent upon the external diameter of the product).
Storage & Installation	For long term storage keep away from direct sunlight to avoid product degradation, over 12 months exposure to direct sunlight should be avoided. Special protective measures will be required in installation than more robust systems for successful performance.

DUCT						
OD (mm)	Effective Length (m)	Nominal Wall Thickness (mm)	Min Socket Length (mm)	Code	Pack Quantity	Nominal Pipe Weight (kg/m)
54 (2in)	6	1.8	50	T101379	369	0.38
88.9 (3in)	6	1.9	70	T101380	125	0.80
114 (4in)	6	2.0	80	T101381	76	1.17
168 (6in)	6	2.7	100	T101382	39	2.22

Get in touch

Address: Naylor Specialist Plastics, Unit 47, Coneygre Industrial Estate, Coneygre Road, Tipton, DY4 8XP
 Email: specialistplastics@naylor.co.uk
 Phone: 0121 522 0290





HDPE General Purpose Duct

HDPE general purpose duct is a single wall pipe manufactured under ISO 9001:2015. HDPE general purpose duct is produced with loose push-fit sockets, using an unsealed system.

Material	High Density Polyethylene (HDPE)
Colour	Available in black. Other colours available on request.
Marking	NAYLOR GP DUCT SIZE x 6m dd-mm-yy TIME
Quality System & Inspection	All quality systems and inspection procedures comply with BS EN ISO 9001: 2015
Standards & Certification	Does not meet the requirements of BS EN 61386-24:2010
Packaging	Supplied in 6 metre lengths (with loose pushfit coupler on one end), in timber u-frame packs. Quantities per pack as detailed below in chart.
Storage & Installation	Suitable to be stored outside, try to keep out of direct sunlight where possible. Special protective measures will be required in installation compared to more robust systems for successful performance.

DUCT						
OD (mm)	Effective Length (m)	Nominal Wall Thickness (mm)	Loose Pushfit Coupler	Code	Pack Quantity	Nominal Pipe Weight (kg/m)
54 (2in)	6	2.25	Yes	T101164	369	0.30
88.9 (3in)	6	2.25	Yes	T101172	125	0.69
114 (4in)	6	2.25	Yes	T101170	76	0.82
168 (6in)	6	3.0	Yes	T101194	39	1.46
200 (8in)	6	5.5	Yes	T101182	25	3.47
250 (10in)	6	5.5	Yes	T101265	16	5.08
110 (4in)	6	2.25	Yes	T101173	76	0.79
160 (6in)	6	3.0	Yes	T101180	39	1.25

Get in touch

Address: Naylor Specialist Plastics, Unit 47, Coneygre Industrial Estate, Coneygre Road, Tipton, DY4 8XP
 Email: specialistplastics@naylor.co.uk
 Phone: 0121 522 0290

